

In the claims

Claims 1-17 (canceled)

1 18. (Original) A magnetic read head which has an air bearing surface
2 (ABS), comprising:
3 a tunnel junction sensor including:
4 a ferromagnetic pinned layer structure that has a magnetic moment;
5 an antiferromagnetic pinning layer exchange coupled to the pinned layer
6 structure for pinning the magnetic moment of the pinned layer structure;
7 a ferromagnetic free layer structure which has a magnetic moment;
8 a nonmagnetic electrically insulative barrier layer located between the free
9 layer structure and the pinned layer structure; and
10 the pinned layer structure or the free layer structure having an oxidized
11 monolayer that is adjacent the barrier layer.

1 19. (Original) A magnetic read head as claimed in claim 18 wherein the
2 pinned layer structure includes a cobalt based layer that has said oxidized monolayer.

1 20. (Original) A magnetic read head as claimed in claim 19 wherein the
2 cobalt based layer is cobalt iron (CoFe).

1 21. (Original) A magnetic read head as claimed in claim 20 including:
2 ferromagnetic first and second shield layers; and
3 the tunnel junction sensor being located between the first and second shield
4 layers.

1 22. (Original) A magnetic head assembly having an air bearing surface
2 (ABS), comprising:
3 a write head including:
4 ferromagnetic first and second pole piece layers that have a yoke portion
5 located between a pole tip portion and a back gap portion;
6 a nonmagnetic write gap layer located between the pole tip portions of the
7 first and second pole piece layers;

8 an insulation stack with at least one coil layer embedded therein located
9 between the yoke portions of the first and second pole piece layers; and
10 the first and second pole piece layers being connected at their back gap
11 portions; and
12 a read head including:
13 a first shield layer;
14 a tunnel junction sensor located between the first shield layer and the first
15 pole piece layer;
16 the tunnel junction sensor including:
17 a ferromagnetic pinned layer structure that has a magnetic moment;
18 an antiferromagnetic pinning layer structure exchange coupled to the
19 pinned layer structure for pinning the magnetic moment of the pinned layer
20 structure;
21 a ferromagnetic free layer structure which has a magnetic moment; and
22 a nonmagnetic electrically insulative barrier layer located between the free
23 layer structure and the pinned layer structure; and
24 the pinned layer structure or the free layer structure having an oxidized
25 monolayer that is adjacent the barrier layer.

1 23. (Original) A magnetic head assembly as claimed in claim 22 wherein
2 the pinned layer structure includes a cobalt based layer that has said oxidized monolayer.

1 24. (Original) A magnetic head assembly as claimed in claim 23 wherein
2 the cobalt based layer is cobalt iron (CoFe).

1 25. (Original) A magnetic head assembly as claimed in claim 24
2 including:
3 ferromagnetic first and second shield layers; and
4 the tunnel junction sensor being located between the first and second shield
5 layers.

1 26. (Original) A magnetic disk drive including at least one magnetic head
2 assembly that has an a write head, a read head and an air bearing surface (ABS)
3 comprising:

4 the write head including:

5 ferromagnetic first and second pole piece layers that have a yoke portion
6 located between a pole tip portion and a back gap portion;

7 a nonmagnetic write gap layer located between the pole tip portions of the
8 first and second pole piece layers;

9 an insulation stack with at least one coil layer embedded therein located
10 between the yoke portions of the first and second pole piece layers; and

11 the first and second pole piece layers being connected at their back gap
12 portions; and

13 the read head including:

14 a first shield layer;

15 a tunnel junction sensor located between the first shield layer and the first
16 pole piece layer;

17 the tunnel junction sensor including:

18 a ferromagnetic pinned layer structure that has a magnetic moment;

19 an antiferromagnetic pinning layer exchange coupled to the pinned layer
20 structure for pinning the magnetic moment of the pinned layer structure;

21 a ferromagnetic free layer structure which has a magnetic moment;

22 a nonmagnetic electrically insulative barrier layer located between the free
23 layer structure and the pinned layer structure; and

24 the pinned layer structure or the free layer structure having an oxidized
25 monolayer that interfaces the barrier layer;

26 a housing;

27 a magnetic disk rotatably supported in the housing;

28 a support mounted in the housing for supporting the magnetic head assembly with
29 said ABS facing the magnetic disk so that the magnetic head assembly is in a transducing
30 relationship with the magnetic disk;

31 a spindle motor for rotating the magnetic disk;

32 an actuator positioning means connected to the support for moving the magnetic
33 head assembly to multiple positions with respect to said magnetic disk; and

34 a processor connected to the magnetic head assembly, to the spindle motor and
35 to the actuator for exchanging signals with the magnetic head assembly, for controlling
36 movement of the magnetic disk and for controlling the position of the magnetic head
37 assembly.

1 27. (Original) A magnetic disk drive as claimed in claim 26 wherein the
2 pinned layer structure includes a cobalt based layer that has said oxidized monolayer.

1 28. (Original) A magnetic disk drive as claimed in claim 27 wherein the
2 cobalt based layer is cobalt iron (CoFe).

1 29. (Original) A magnetic disk drive as claimed in claim 27 including:
2 ferromagnetic first and second shield layers; and
3 the tunnel junction sensor being located between the first and second shield
4 layers.